

Package: psychds (via r-universe)

October 16, 2026

Title Tools for Creating and Validating 'Psych-DS' Datasets

Version 0.1.0

Description Provides a 'Shiny' application and helper functions for adopting 'Psych-DS' (<<https://psych-ds.github.io/>>), a community data standard for organizing and documenting datasets in the psychological and behavioral sciences inspired by the Brain Imaging Data Structure ('BIDS'). A guided interface walks researchers through the dataset creation process, organizing tabular data files into proper 'Psych-DS' directory structures, generating new, compliant, keyword-based filenames, and generating machine-readable 'JSON' metadata. Additional tools support building and editing data dictionaries with variable-level descriptions, validating datasets against the full 'Psych-DS' specification via a bundled 'JavaScript' validator, and exploring dataset contents interactively.

License MIT + file LICENSE

URL <https://psych-ds.github.io/psychds-r/>,
<https://github.com/psych-ds/psychds-r>

BugReports <https://github.com/psych-ds/psychds-r/issues>

Copyright see file inst/COPYRIGHTS for bundled 'JavaScript' library copyrights and licenses

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Depends R (>= 4.1.0)

Imports cli, jsonlite, rstudioapi, shiny (>= 1.7.0), tools, utils

Suggests crosstalk, DT, fs, knitr, miniUI, pointblank, rmarkdown, shinydashboard, shinyjs, sortable, spelling, testthat (>= 3.0.0), zip

Config/testthat/edition 3

SystemRequirements Node.js (>= 18.0.0)

VignetteBuilder knitr
Language en-US
Config/pak/sysreqs cmake make libuv1-dev zlib1g-dev
Repository https://psych-ds.r-universe.dev
Date/Publication 2026-09-21 16:04:08 UTC
RemoteUrl https://github.com/psych-ds/psychds-r
RemoteRef HEAD
RemoteSha 21ac89b59d95c6e55d671dc83b6246511247be78

Contents

check_dependencies	2
check_psychds_deps	3
run_app_safe	4
run_psych_ds_app	4
validate_dataset	6
Index	7

check_dependencies	<i>Check and Load Package Dependencies</i>
--------------------	--

Description

This function provides robust package management following CRAN policies. It checks versions, handles conflicts, and provides clear user feedback.

Usage

```
check_dependencies(  
  min_versions = NULL,  
  recommended_versions = NULL,  
  startup_mode = getOption("psychds.startup_mode", "recommended")  
)
```

Arguments

- min_versions Named list of minimum required package versions
- recommended_versions
 Named list of recommended package versions
- startup_mode Character: "strict", "recommended", or "minimal"

Value

Logical indicating success

check_psychds_deps	<i>Check psychds Dependencies</i>
--------------------	-----------------------------------

Description

Verifies that all required and optional package dependencies are installed and meet minimum version requirements.

Usage

```
check_psychds_deps(  
  install_missing = interactive(),  
  detailed = FALSE,  
  check_pdf = TRUE  
)
```

Arguments

install_missing	Logical. If TRUE (and session is interactive), prompts the user to install any missing packages. Defaults to <code>interactive()</code> .
detailed	Logical. If TRUE, displays additional information about the R environment. Default is FALSE.
check_pdf	Logical. Ignored. Retained for backwards compatibility. Default is TRUE.

Details

This function checks for:

- Required packages: shiny, shinydashboard, shinyjs, DT, jsonlite
- Optional packages: sortable, zip, pointblank
- Minimum version requirements for each package

If dependencies are missing, the function provides installation instructions.

Value

Invisibly returns a list with `missing_required` and `missing_recommended` character vectors.

Examples

```
# Quick check  
check_psychds_deps()  
  
# Detailed check with environment info  
check_psychds_deps(detailed = TRUE)
```

run_app_safe	<i>Initialize Shiny App with Robust Package Management</i>
--------------	--

Description

Main entry point that ensures all dependencies are met

Usage

```
run_app_safe(app_dir = system.file("shiny", package = "psychds"), ...)
```

Arguments

app_dir	Directory containing the Shiny app
...	Additional arguments passed to shiny::runApp

run_psych_ds_app	<i>Run the Psych-DS Shiny Application</i>
------------------	---

Description

Launches the interactive Shiny application for creating, editing, and validating Psych-DS compliant datasets.

Usage

```
run_psych_ds_app(
  launch.browser = getOption("shiny.launch.browser", interactive()),
  port = getOption("shiny.port"),
  host = getOption("shiny.host", "127.0.0.1"),
  startup_mode = getOption("psychds.startup_mode", "recommended"),
  force_browser = getOption("psychds.force_browser", FALSE),
  ...
)
```

Arguments

launch.browser	Logical or function. Should the app be opened in a browser? Defaults to TRUE in interactive sessions.
port	Integer. Port number for the application. If NULL, a random available port is used.
host	Character. Host IP address. Defaults to "127.0.0.1" (localhost).
startup_mode	Character. One of "strict", "recommended", or "minimal". Controls dependency checking strictness:

- "strict": Requires all packages at minimum versions
 - "recommended": Warns about outdated packages but continues
 - "minimal": Only checks for critical dependencies
- force_browser Logical. Force opening in external browser. Recommended for RStudio users experiencing viewer issues.
- ... Additional arguments passed to [shiny::runApp\(\)](#).

Details

The application provides a guided interface for:

- Selecting project directories and data files
- Adding dataset metadata
- Standardizing filenames with Psych-DS keywords
- Generating data dictionaries
- Validating datasets against the Psych-DS specification

Value

This function does not return a value. It launches the Shiny application and blocks until the app is closed.

See Also

[check_psychds_deps\(\)](#) for verifying dependencies before running.

Examples

```
## Not run:
# Standard launch
run_psych_ds_app()

# Force external browser (if RStudio viewer has issues)
run_psych_ds_app(force_browser = TRUE)

# Minimal checking for faster startup
run_psych_ds_app(startup_mode = "minimal")

# Specific port
run_psych_ds_app(port = 3838)

## End(Not run)
```

validate_dataset	<i>Validate a Psych-DS Dataset</i>
------------------	------------------------------------

Description

Validates a dataset directory against the full 'Psych-DS' specification using the same validator used by the 'psychds-validator' command-line tool.

Usage

```
validate_dataset(dir_path, json = FALSE, verbose = FALSE, use_events = FALSE)
```

Arguments

dir_path	Path to the 'Psych-DS' dataset directory to validate.
json	Logical. If TRUE, output results as JSON instead of formatted text. Default is FALSE.
verbose	Logical. If TRUE, show verbose output including warnings. Default is FALSE.
use_events	Logical. If TRUE, show live checklist progress output. Default is FALSE.

Details

Requires 'Node.js' to be installed and available on the system PATH. Install 'Node.js' from <https://nodejs.org>.

Value

Invisibly returns the exit status. Called for its side effect of printing validation results to the console.

Examples

```
## Not run:
# Standard text output
validate_dataset("path/to/my-study")

# JSON output for programmatic use
validate_dataset("path/to/my-study", json = TRUE)

# Verbose with warnings
validate_dataset("path/to/my-study", verbose = TRUE)

# Live checklist
validate_dataset("path/to/my-study", use_events = TRUE)

## End(Not run)
```

Index

`check_dependencies`, [2](#)
`check_psychds_deps`, [3](#)
`check_psychds_deps()`, [5](#)

`run_app_safe`, [4](#)
`run_psych_ds_app`, [4](#)

`shiny::runApp()`, [5](#)

`validate_dataset`, [6](#)